

# **PFINDER 890** REMOVER

PFINDER KG Rudolf-Diesel-Strasse 14 71032 Böblingen/Germany + 49 (0) 7031-2701-999 ndt@pfinder.de www.pfinder-ndt.com

Version 3 / 01 03 2017

## DESCRIPTION

PFINDER 890 is a special cleaner based on isopropanol / acetone for penetrant and magnetic particle testing. PFINDER 890 is used as precleaner for removal of oils and greases from the surface to be tested, as approved remover of PFINDER penetrants or as remover of PFINDER contrast paint.

PFINDER 890 is particulary suitable for general cleaning and removal of oils and greases. Material compartibibility (e.g. for plastics) has to be checked beforehand.

Remover method C according EN ISO 3452-1.

## APPLICATION

For precleaning or as all-purpose cleaner: Applicate PFINDER 890 to the surface to be cleaned, if necessary allow time to react and if required wipe off with a cloth.

For excess penetrant removal: Spray PFINDER 890 on a cloth and clean surface to be tested. Do not spray directly on the surface!

For removal of PFINDER contrast paint: Spray on surface to be cleaned, if necessary allow time to react and remove paint by wiping off with a cloth or by additional spraying.

The capability of the penetrant system should be checked regularly by means of own reference pieces or e.g. reference test block 2 according EN ISO 3452-3.



# YOUR GREEN NDT BENEFITS

Aerosol spray can with minimized carbon footprint



## YOUR HANDLING + COST SAVING BENEFITS

- Powerful cleaner
- All-purpose use

#### **PACKAGES IN STOCK / STORAGE CONDITIONS**

500-mL-spray can (for 360° application), 5-L-canister. These packages are on stock and instantly available. Other packages on demand.

ASTM D 93

Storage between +5°C and +45°C.

## **TECHNICAL PROPERTIES**

Density/20°C Flash point

DIN EN ISO 12185 795 ± 15 kg/m<sup>3</sup> <15°C

Data of products packaged in aerosol spray cans might differ.

The information contained herin is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest to evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence, or otherwise is limited to the purchase price of the material.



#### **APPROVALS & CONFORMITIES**

The product conforms to the following specifications / is suitable for use according to:

EN ISO 3452-2, 3452-6, ASTM E165, ASME V Art.6, PMUC, RCC-M.

Low content of sulfur and halogens according to EN ISO 3452-2.

> Please respect the relevant rules and specifications for your application.

## SHELF-LIFE

2 years Spray cans: 3 years